

BIPV in the Inside Out project, a plus energy retrofit of a high-rise apartment building




Wilfried van Sark
Eelke Bontekoe

Utrecht University
Inside Out Technologies



Universiteit Utrecht



Social housing renovation


Energy demand 2019
Electricity
Gas (heating, cooking)



Energy demand 2021
Electricity
Energy positive



Utrecht, the Netherlands





Integration

Heatpumps on the roof
Hidden underneath a *PV pergola*

Facades:

- BAPV
- Per apartment BIPV, glass-glass, semitransparent and grey



Grey panel (RAL7030)

Ceramic coating on outside

- 35% loss of light
- 66 mono cells
- 340 Wp → 220 Wp



Overview of the PV system


Location	Type	P_peak (Wp)	Modules Installed	Total Installed Capacity (kWp)
SE Facade	Grey, BIPV	160 - 220	160	31.2
SE Balcony	Semi-transparent	300	116	34.8
NE Facade	Black	340	160	54.4
SW Facade	Black	340	160	54.4
SE Crown	Black	340	116	39.4
NW Crown	Black	340	116	39.4
SE Roof 18°	Black	355	174	61.8
NW Roof 28°	Black	355	116	41.2
Total			1118	356.6

Energy balance

2023 (Sankey diagram):

- Supply 216.9 MWh
- Demand 178.2 MWh
- **SURPLUS: 38.7 MWh**

Specific yield 608 kWh/kWp



(Bontekoe, Lampropoulos, Van Sark, in preparation)



Thank you!

This is an initiative of



Co-funded by
the European Union

Grant N°101096126. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or CINEA. Neither the European Union nor the granting authority can be held responsible for them.

Project funded by



Schweizerische Eidgenossenschaft
Confédération suisse
Confederazione Svizzera
Confederaziun svizra

Swiss Confederation

Federal Department of Economic Affairs,
Education and Research EAER
State Secretariat for Education,
Research and Innovation SERI